

小型安规测试仪选型表

参数/型号	MI3309	MI3311	MI3310	MI3310A	MI2142	MI3304	MI3305
测量							
连续性 200mA	●	●	●	●	●	●	●
连续性 10A				●	●	●	●
连续性 25A					●	●	●
直流绝缘电阻 250V DC	●	●	●	●	●	●	●
直流绝缘电阻 500V DC	●	●	●	●	●	●	●
差分泄漏电流	●		●	●	●	●	●
触摸泄漏电流	●		●	●	●	●	●
替代泄漏电流	●	●	●	●	●	●	●
可选电流钳泄漏电流测量			●	●	●	●	●
瞬态测试 (闪测)							●
PRCD 测试	●		●	●		●	●
极性测试 (IEC 电源线测试)	●	●	●	●	●	●	●
功能测试 (负荷)	●		●	●	●	●	●
其它特征							
通过/不通过 评价	●	●	●	●	●	●	●
电源自动检查	●	●	●	●	●	●	●
图形 LCD 显示	●	●	●	●	●	●	●
图形在线帮助	●	●	●	●	●	●	●
背光	●	●	●	●	●	●	●
实时时钟	●	●	●	●	●	●	●
标准键盘			●	●	●	●	●
自动测试 (标准和定制)	●	●	●	●		●	●
条码捷径自动测试	●	●	●	●	●	●	●
RS232/USB 通讯接口	●/●	●/●	●/●	●/●	●/可选	●/●	●/●
蓝牙通讯接口				●			
条码输入+标签打印	●		●	●	●	●	●
数据下载到 PC	●	●	●	●	●	●	●
从 PC 下载数据			●	●	●	●	●
在仪器液晶屏显示趋势 (对比)			●	●	●	●	●
计算机软件显示数据趋势			●	●	●	●	●
保存数据量	3000	1500	6000	6000	1100	6500	6500
标准配置及可选件							
条码扫描仪	可选	可选	可选	可选	可选	可选	可选
标签打印机	可选		可选	可选		可选	可选
票据打印机			可选	可选		可选	可选
PC SW	●	可选	●	●	●	●	●
增强 PC SW	可选	可选	可选	可选	可选	可选	可选
通用技术参数							
重量	1.2 公斤	0.86 公斤	5 公斤	5.8 公斤	3.5 公斤	8.4 公斤	8.4 公斤
尺寸	140 × 80 × 230	140 × 80 × 230	310 × 130 × 250	310 × 130 × 250	265 × 110 × 185	345 × 160 × 335	345 × 160 × 335
电池供电	6 节 5 号	6 节 5 号	6 节 2 号	6 节 2 号			
交流电源	●		●	●	●	●	●